

**AMENDMENTS TO THE CLAIMS**

---

1. (Currently Amended) A cleaning and releasing device for spraying a jet flow onto an object to be cleaned, comprising:

an injection nozzle;

operating means for supplying and stopping a pressurized liquid to said injection nozzle, said operating means being provided in said injection nozzle or in ~~the vicinity thereof~~ communication therewith; and

detecting means for detecting supply and stop of the pressurized liquid generated by an operation of said operating means, said detecting means being provided in a ~~proper~~ position on a flow passage of the pressurized liquid;

wherein the supply and stop of a pressurized gas to said injection nozzle is controlled based on a result of the detection by said detecting means.

Q4 2. (Currently Amended) A cleaning and releasing device according to claim 1, ~~further comprising:~~ wherein said operating means comprises a hand valve provided on the flow passage of the pressurized liquid in said injection nozzle or in ~~the vicinity thereof~~ communication therewith and serving to supply and stop the pressurized liquid to the injection nozzle ~~[[;]]~~ , and said cleaning and releasing device further comprises:

a switching valve provided in a ~~proper~~ position on a flow passage of the pressurized gas and serving to supply and stop the pressurized gas to the injection nozzle; and

~~flow detecting means provided in a proper position on the flow passage of the pressurized liquid and serving to detect presence of a flow of the liquid; and~~

a controller for controlling a switching operation of the switching valve based on a result of the detection transmitted from the ~~flow~~ detecting means;

wherein the switching valve is controlled to ~~the~~ supply and stop the pressurized gas depending on the presence of the flow of the pressurized liquid generated by a switching operation of the hand valve.

3. (Original) A cleaning and releasing device according to claim 1, further comprising powder and granular supply means being provided on a flow passage of the pressurized gas, and supply and stop of the powder and granular material is controlled based on a result of the detection related to the supply and stop of the pressurized liquid to said injection nozzle.

4. (Original) A cleaning and releasing device according to claim 3, wherein the supply of the pressurized gas is started and the supply of the powder and granular material is started based on the detection of the supply of the pressurized liquid to said injection nozzle when injection is to be started, the supply of the powder and granular material is stopped and the supply of the pressurized gas is stopped after a predetermined time passes based on the detection of the stop of the pressurized liquid to said injection nozzle when the injection is to be stopped.

AK 5. (Currently Amended) A cleaning and releasing device for sucking a gas through a jet flow of a pressurized liquid supplied to an injection nozzle and for spraying a jet flow formed by supplying a powder and granular material ~~in a proper process~~ onto an object to be cleaned, said device comprising:

operating means for operating supply and stop of a pressurized liquid, said operating means being provided in said injection nozzle or in ~~the vicinity thereof~~ communication therewith; and

detecting means for detecting the supply and stop of the pressurized liquid generated by an operation of said operating means, said detecting means being provided in a ~~proper~~ position on a flow passage of the pressurized liquid;

wherein supply and stop of the powder and granular material is controlled based on a result of the detection by said detecting means.

6. (Currently Amended) A cleaning and releasing device comprising:

- a liquid tank for storing liquid;
- a pump for pressurizing the liquid in said liquid tank to supply pressurized liquid;
- a liquid supply passage for connecting said liquid tank to said pump;
- an injection nozzle for injecting the pressurized liquid;
- a pressurized liquid flow passage for connecting said pump to said injection nozzle;
- a pressurized gas source;
- a pressurized gas supply passage for connecting said pressurized gas source to said injection nozzle;

a sensor provided on one of said liquid supply passage and said pressurized liquid flow passage to detect supply and stop of the pressurized liquid from said liquid tank;

an operating portion disposed in said injection nozzle or ~~in the vicinity thereof~~ on said pressurized liquid flow passage to thereby supply and stop the pressurized liquid; and

a controller connected to said sensor and said pressurized gas supply passage, said controller detecting supply and stop of the pressurized liquid detected by said sensor to thereby control supply and stop of the pressurized gas from said pressurized gas supply passage to said injection nozzle based on a result of a detection by said sensor.

7. (Original) A cleaning and releasing device according to claim 6, further comprising a powder and granular material tank connected to said pressurized gas supply passage, and supply and stop of powder and granular material is controlled by said controller based on the supply and stop of the pressurized liquid detected by said sensor.

8. (Withdrawn) A cleaning and releasing device comprising:

- a liquid tank for storing liquid;
- a pump for pressurizing the liquid in said liquid tank to supply pressurized liquid;
- a liquid supply passage for connecting said liquid tank to said pump;
- an injection nozzle for injecting the pressurized liquid;
- a pressurized liquid flow passage for connecting said pump to said injection nozzle;

an air supply passage connected to said injection nozzle, said air supply passage sucking air from outside based on an ejector effect of a jet flow of the pressurized liquid;

a sensor provided on one of said liquid supply passage and said pressurized liquid flow passage to detect supply and stop of the pressurized liquid from said liquid tank;

a powder and granular material tank connected to said air supply passage and supplying powder and granular material;

an operating portion disposed in said injection nozzle or in the vicinity thereof on said pressurized liquid flow passage to thereby supply and stop the pressurized liquid; and

a controller connected to said sensor and said pressurized gas supply passage, said controller detecting supply and stop of the pressurized liquid detected by said sensor to thereby control supply and stop of the powder and granular material from said powder and granular material tank to air supply passage based on a result of a detection by said sensor.

9. (New) A cleaning and releasing device according to claim 1, wherein the supply and stop of the pressurized gas to said injection nozzle is controlled based on the respective supplying and stopping of the pressurized liquid, as detected by said detecting means.

10. (New) A cleaning and releasing device according to claim 5, wherein the supply and stop of the powder and granular material is controlled based on the respective supplying and stopping of the pressurized liquid, as detected by said detecting means.

11. (New) A cleaning and releasing device according to claim 6, wherein said controller controls the supply and stop of the pressurized gas from said pressurized gas supply passage to said injection nozzle based on the respective supply and stop of the pressurized liquid as detected by said sensor.